

Yii2 Config

- [Disable GII](#)
- [Launchpad](#)
- [Arahan Untuk Setiap Servis](#)
- [Secure Cookies](#)

Disable GII

Gii code generator can be disabled by adjusting config for either frontend and backend.

- **Frontend**

1. Go to `app/frontend/config/main-local.php`
2. Comment or remove this line.

```
if (!YII_ENV_TEST) {  
    $config['bootstrap'][] = 'debug';  
    $config['modules']['debug'] = [  
        'class' => 'yii\debug\Module',  
    ];  
    $config['bootstrap'][] = 'gii';  
    $config['modules']['gii'] = [  
        'class' => 'yii\gii\Module',  
    ];  
}
```

- **Backend**

1. Go to `app/backend/config/main-local.php`
2. Comment or remove this line.

```
if (!YII_ENV_TEST) {  
    $config['bootstrap'][] = 'debug';  
    $config['modules']['debug'] = [  
        'class' => 'yii\debug\Module',  
    ];  
    $config['bootstrap'][] = 'gii';  
    $config['modules']['gii'] = [  
        'class' => 'yii\gii\Module',  
    ];  
}
```

Launchpad

<https://launchpad.net/ubuntu/+archivemirrors>

Arahan Untuk Setiap Servis

Nginx Service

```
# Start Nginx
sudo systemctl start nginx

# Stop Nginx
sudo systemctl stop nginx

# Restart Nginx
sudo systemctl restart nginx

# Reload Nginx (without downtime)
sudo systemctl reload nginx
```

MySQL Service

```
# Start MySQL
sudo systemctl start mysql

# Stop MySQL
sudo systemctl stop mysql

# Restart MySQL
sudo systemctl restart mysql
```

PHP 8.3-FPM Service

```
# Start PHP-FPM
sudo systemctl start php8.3-fpm

# Stop PHP-FPM
sudo systemctl stop php8.3-fpm
```

```
# Restart PHP-FPM
sudo systemctl restart php8.3-fpm
```

Lihat status setiap servis

```
sudo systemctl status service_name
# Example: sudo systemctl status nginx
```

Secure Cookies

```
'session' => [  
    [] 'name' => 'FrontendSessionPetra',  
        'cookieParams' => [  
            'httpOnly' => true,  
            'secure' => true  
        ]  
    ],  
    'cookies' => [  
    [] 'cookieValidationKey' => '55842521143P0o&&YjFFPetra',  
        'csrfParam' => '_backendCSRF',  
        'class' => 'yii\web\Cookie',  
        'httpOnly' => true,  
        'secure' => true  
    ],  
    'request' => [  
        'csrfCookie' => [  
            'httpOnly' => true,  
            'secure' => true  
        ]  
    ],  
    'user' => [  
        'identityClass' => 'common\models\FrontendUser',  
        'enableAutoLogin' => true,  
    [] [] 'identityCookie' => [  
        'name' => '_identity',  
        'httpOnly' => true,  
        'secure' => true,  
    ],  
    ],  
],
```

Header always edit Set-Cookie ^(.*)\$ "\$1; HttpOnly; SameSite=Lax; Secure"